

Claims

1. A molten metal transporting container comprising:

5 a long-reach-pouring spout connected to a pouring outlet of a pouring spout and projects toward the outside of the container body,

a spout operating member for separating the long-reach-pouring spout from the pouring spout by raising
10 the long-reach-pouring spout while the long-reach-pouring spout is projected from the container body, and

a spout drawing member for drawing the long-reach-pouring spout that was separated from the pouring spout toward the container body.

15

2. A molten metal transporting container according to Claim 1, wherein the spout drawing member is provided with a rotation shaft for drawing the long-reach-pouring spout that was separated from the pouring spout
20 toward the container body by rotating it.

3. A molten metal transporting container according to Claim 2, wherein the pouring spout is provided with a protrusion or concave portion for aligning
25 the pouring spout with the long-reach-pouring spout, and the long-reach-pouring spout is provided with a protrusion or concave portion that fits in the protrusion or concave portion of the pouring spout in such a manner that the distance between the pouring spout and the long-reach-pouring spout that was separated from the pouring spout is
30 greater than the height of the protrusion.

4. A molten metal transporting container according to Claim 2 or 3, wherein the rotation shaft is
35 suspended from the long-reach-pouring spout, and a hole

into which the rotation shaft can be loosely fit is provided in the pouring spout;

the molten metal transporting container further comprising a spout operating member that separates the
5 long-reach-pouring spout from the pouring spout by raising the rotation shaft and connects the long-reach-pouring spout to the pouring spout by lowering the rotation shaft.